UK RANGE & ORDERING GUIDE

FEIN POWER TOOLS

Metal fabrication, assembly and workshop tooling



CHOOSE BY JOB

RANGE	APPLICATION	PAGE
Drilling & fastening	Drill, tap, drive fixings or control assembly torque.	02–04
Magnetic drilling	Core drill steel plate and structural sections.	05–06
Grinding & finishing	Cut, grind, deburr or polish with handheld tools.	07–10
GRIT belt grinding	Set up stationary belt, surface and tube grinding.	11–13
Sawing & sheet metal	Cut sheet, profiles or pipe, and follow curves.	14–15
Bevelling & pipe milling	Prepare edges, chamfers and pipe ends.	16
Oscillating tools	Plunge-cut, scrape, sand or remove vehicle glazing.	17–19
Extraction & workholding	Extract dust, clamp parts or suspend hand tools.	20–23
Batteries & accessories	Match the battery, mount, tooling and consumables.	24–25

Order by FEIN code

Follow the order code to the exact FEIN product page for its complete specifications, supplied items and compatible accessories. Check the supply or battery platform and kit contents before ordering.

FEIN UK machine catalogue

© R H Davey Welding Supplies Ltd · Design and editorial content

DRILLING & FASTENING

Drill/Drivers & Hammer Drill

Compare chuck, torque and steel drilling capacity. Choose the SDS-plus rotary hammer for masonry and concrete.



99100001552



71161566000



71400361000

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
ASCM 18 QSW AS cordless drill/driver (in box)	99100001552	18 V AMPShare	Torque 40 / 30 Nm	Boxed tool
ASCM 18-4 QM AS cordless drill/driver (in box)	99100001551	18 V AMPShare	Torque 130 (70 / 50) Nm · Steel Ø 13mm	Boxed tool
ASCM 18-4 QMP AS cordless hammer drill/driver (in box)	99100001553	18 V AMPShare	Torque 130 (70 / 50) Nm · Steel Ø 13mm	Boxed tool
Cordless drill driver ABS 18 Q AS	71132461000	18 V AMPShare	Torque 60 / 38 Nm · Steel Ø 13 mm	Case included
Cordless drill driver ASCM 18 QSW AS	71161461000	18 V AMPShare	Torque 40 / 30 Nm	Case included
Cordless drill driver ASCM 18-4 QM AS Metal Advanced Set	71161564000	18 V AMPShare	Torque 130 (70 / 50) Nm · Steel Ø 13mm	Case included
Cordless drill driver ASCM 18-4 QM AS QuickIN Set	71161566000	18 V AMPShare	Torque 130 (70 / 50) Nm · Steel Ø 13mm	Case included
Cordless drill/driver ABS 18 Q AS (in box)	99100001555	18 V AMPShare	Torque 60 / 38 Nm · Steel Ø 13 mm	Boxed tool
Cordless drill/driver ASCM 18-4 QM AS	71161561000	18 V AMPShare	Torque 130 (70 / 50) Nm · Steel Ø 13mm	Case included
Cordless drill/driver ASCM 18-4 QMP AS	71161661000	18 V AMPShare	Torque 130 (70 / 50) Nm · Steel Ø 13mm	Case included
Cordless impact drill driver ASB 18 Q AS	71040761000	18 V AMPShare	Torque 60 / 38 Nm · Steel Ø 13 mm	Case included
Cordless impact drill/driver ASB 18 Q AS (in box)	99100001557	18 V AMPShare	Torque 60 / 38 Nm · Steel Ø 13 mm	Boxed tool
ABH 18-26 AS cordless hammer drill	71400361000	18 V AMPShare	Concrete Ø 26mm · Mount SDS-plus	Case included

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

DRILLING & FASTENING

Impact Tools & Combo Kits

Select the square drive or hex interface for your sockets and bits. Check the supplied batteries and charger for each kit.



71151161000



71151065000



99100000837

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
ASCD 18-200 W4 AS cordless impact wrench	71151161000	18 V AMPShare	Torque 210 Nm · Drive 1/4 in hexagon socket	Case included
ASCD 18-300 W2 AS cordless impact wrench	71151061000	18 V AMPShare	Torque 290 Nm · Drive 1/2" Outer square · Metric screw M18 (8.8)	Case included
ASCD 18-300 W2 AS cordless impact wrench (in box)	99100001554	18 V AMPShare	Torque 290 Nm · Drive 1/2" Outer square · Metric screw M18 (8.8)	Boxed tool
Cordless impact driver ASCD 18-200 W4 AS (in box)	99100001556	18 V AMPShare	Torque 210 Nm · Drive 1/4 in hexagon socket	Boxed tool
Cordless impact wrench ASCD 18-1000 W34 AS	71151261000	18 V AMPShare	Torque 1 050 Nm · Drive 3/4 in square · Metric screw M27 (8.8)	Case included
Cordless impact wrench ASCD 18-300 W2 AS Impact tapping set	71151065000	18 V AMPShare	Torque 290 Nm · Drive 1/2" Outer square · Metric screw M18 (8.8)	Case included
Cordless impact wrench ASCD 18-300 W2 AS Ready-to-use set	71151063000	18 V AMPShare	Torque 290 Nm · Drive 1/2" Outer square · Metric screw M18 (8.8)	Case included
AMM 500 cordless MULTIMASTER & ASCM 18 QSW AS cordless drill/driver	99100000838	18 V AMPShare	—	Cordless value combo
ASCD 18-200 W4 cordless impact wrench/driver & ASCM 18 QSW cordless drill/driver	99100000835	18 V AMPShare	—	Cordless value combo
ASCM 18-4 QM AS cordless drill/driver & CCG 18-125-12 cordless angle grinder	99100000837	18 V AMPShare	—	Cordless value combo

© R H Davey Welding Supplies Ltd · Design and editorial content

DRILLING & FASTENING

AccuTec Assembly Tools

Match the assembly tool’s torque range and drive to the fastener and production process. Check the battery interface for each model.



71127960000



71127060000



71126460000

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
ASM 18-12 PC	71127960000	18 V MultiVolt	Torque 3 - 12 Nm · Drive 1/4 in hexagon socket · No-load speed 80 - 900 rpm	See supplied items
ASM 18-3 PC	71127760000	18 V MultiVolt	Torque 0.5 - 3 Nm · Drive 1/4 in hexagon socket · No-load speed 110 - 1,200 rpm	See supplied items
ASM 18-8 PC	71127860000	18 V MultiVolt	Torque 1 - 8 Nm · Drive 1/4 in hexagon socket · No-load speed 110 - 1,200 rpm	See supplied items
ASW 18-12 PC	71126860000	18 V MultiVolt	Torque 3 - 12 Nm · No-load speed 75 - 1,020 rpm	See supplied items
ASW 18-18 PC	71127060000	18 V MultiVolt	Torque 6 - 18 Nm · No-load speed 65 - 900 rpm	See supplied items
ASW 18-30 PC	71126260000	18 V MultiVolt	Torque 12 - 30 Nm · No-load speed 30 - 420 rpm	See supplied items
ASW 18-45 PC	71126360000	18 V MultiVolt	Torque 20 - 45 Nm · No-load speed 25 - 310 rpm	See supplied items
ASW 18-6 PC	71126660000	18 V MultiVolt	Torque 1.2 - 6 Nm · No-load speed 100 - 1,340 rpm	See supplied items
ASW 18-60 PC	71126460000	18 V MultiVolt	Torque 25 - 60 Nm · No-load speed 20 - 230 rpm	See supplied items

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

MAGNETIC DRILLING

Compact & Endurance Drills

Compare compact drills for restricted access and endurance models for repetitive drilling.





99100001274

72732461241

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
AKBC 36 MAGFORCE	99100001274	18 V AMPShare	Carbide Ø 36mm · Core depth 35mm · Shank 3/4 in Weldon · Tapping M 12	Case included
AKBC 36 MAGFORCE Set 2 x 8 Ah	99100001283	18 V AMPShare	Carbide Ø 36mm · Core depth 35mm · Shank 3/4 in Weldon · Tapping M 12	1 x GAL18 V-160 AS rapid charger · 2 ProCORE 18 V 8.0 Ah battery
KBC 36 MAGFORCE (110V)	72732362241	110 V · 1,200 W	Carbide Ø 36mm · Core depth 35mm · Shank 3/4 in Weldon · Tapping M 12	Case included
KBC 36 MAGFORCE (230V)	72732362240	1,200 W	Carbide Ø 36mm · Core depth 35mm · Shank 3/4 in Weldon · Tapping M 12	Case included
KBE 32	72709461240	1,200 W	Carbide Ø 32mm · Core depth 50mm · Shank 3/4 in Weldon	See supplied items
KBE 32 (110 V)	72709461241	110 V · 1,200 W	Carbide Ø 32mm · Core depth 50mm · Shank 3/4 in Weldon	See supplied items
KBE 36 MAGSPEED	72732461240	1,600 W	Carbide Ø 36mm · Core depth 50mm · Shank 3/4 in Weldon	Case included
KBE 36 MAGSPEED (110 V)	72732461241	110 V · 1,600 W	Carbide Ø 36mm · Core depth 50mm · Shank 3/4 in Weldon	Case included

Published carbide diameter and depth are separate limits. Check the cutter and holder combination on the model page.

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

MAGNETIC DRILLING

Universal Drills & Drill Jig

Use a universal drill where the job includes operations such as tapping or countersinking. Check the jig collar diameter if you are fitting an existing drill.



90320223000

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
AKBU 35 PMQW AS	71700461000	18 V AMPShare	Carbide Ø 35mm · Core depth 50(75)* mm · Shank 3/4 in Weldon · Tapping M 14	Case included
KBM 50 U (110 V)	72704061241	110 V · 1,200 W	Carbide Ø 50mm · Core depth 50(75)* mm · Shank 3/4 in Weldon · Tapping M 16	Case included
KBM 65 U (110 V)	72704361241	110 V · 1,300 W	Carbide Ø 65mm · Core depth 50(75)* mm · Shank 3/4 in Weldon · Tapping M 20	Case included
KBU 35 MQW (110 V)	72705661240	110 V · 1,010 W	Carbide Ø 35mm · Core depth 50(75)* mm · Shank 3/4 in Weldon · Tapping M 14	Case included
KBU 35 PQW	72707261000	1,010 W	Carbide Ø 35mm · Core depth 50mm · Shank 3/4 in Weldon · Tapping M 14	Case included
KBU 35 PQW	72707261240	1,010 W	Carbide Ø 35mm · Core depth 50mm · Shank 3/4 in Weldon · Tapping M 14	Case included
KBU 35 QW (110 V)	72705461240	110 V · 1,010 W	Carbide Ø 35mm · Core depth 50mm · Shank 3/4 in Weldon · Tapping M 14	Case included
IBS 16	90320223000	—	Tapping M 12 · Collar Ø 53mm	See supplied items

Published carbide diameter and depth are separate limits. Check the cutter and holder combination on the model page.

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

GRINDING & FINISHING

Cordless Angle Grinders

Compare wheel diameter and switch type, then choose the AMPShare tool or battery kit to suit your setup.



71221561000



71221861000



99100001547

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
CCG 18-115-12 AS cordless angle grinder	71221561000	18 V AMPShare	Wheel Ø 115mm · lock-on switch · No-load 2,500 - 8,500 rpm	Case included
CCG 18-115-12 AS cordless angle grinder (in box)	99100001549	18 V AMPShare	Wheel Ø 115mm · lock-on switch · No-load 2,500 - 8,500 rpm	Boxed tool
CCG 18-115-12 PD AS cordless angle grinder	71221761000	18 V AMPShare	Wheel Ø 115mm · dead-man switch · No-load 2,500 - 8,500 rpm	Case included
CCG 18-115-12 PD-SEC AS Set ProCore	71221962240	18 V AMPShare	Wheel Ø 115mm · No-load 2,500 - 8,500 rpm	2 ProCORE 18 V 8.0 Ah battery · 1 x GAL18 V-160 AS rapid charger
CCG 18-115-12 PD-SEC cordless angle grinder	71221961000	18 V AMPShare	Wheel Ø 115mm · dead-man switch · No-load 2,500 - 8,500 rpm	Case included
CCG 18-125-12 AS cordless angle grinder	71221661000	18 V AMPShare	Wheel Ø 125mm · lock-on switch · No-load 2,500 - 8,500 rpm	Case included
CCG 18-125-12 PD AS cordless angle grinder	71221861000	18 V AMPShare	Wheel Ø 125mm · dead-man switch · No-load 2,500 - 8,500 rpm	Case included
CCG 18-125-12 PD AS cordless angle grinder (in box)	99100001548	18 V AMPShare	Wheel Ø 125mm · dead-man switch · No-load 2,500 - 8,500 rpm	Boxed tool
CCG 18-125-12 PD-SEC AS cordless angle grinder	71222061000	18 V AMPShare	Wheel Ø 125mm · dead-man switch · No-load 2,500 - 8,500 rpm	Case included
CCG 18-125-15 AS cordless angle grinder	71220961000	18 V AMPShare	Wheel Ø 125mm · lock-on switch · No-load 3,400 - 9,800 rpm	Case included
CCG 18-125-7 AS cordless angle grinder	71221361000	18 V AMPShare	Wheel Ø 125mm · lock-on switch · No-load 11,000 rpm	Case included
CCG 18-125-7 AS cordless angle grinder (in box)	99100001550	18 V AMPShare	Wheel Ø 125mm · lock-on switch · No-load 11,000 rpm	Boxed tool
Cordless angle grinder CCG 18-125-12 AS (in box)	99100001547	18 V AMPShare	Wheel Ø 125mm · lock-on switch · No-load 2,500 - 8,500 rpm	Boxed tool

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

GRINDING & FINISHING

Mains Angle Grinders

Choose the wheel diameter, switch and supply for the work. Quote the exact order code for 110 V variants.



72251660241



72250960240

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
Angle grinder AlphaGrind LG 24-230 D Pro (110 V)	72251660241	110 V · 2,400 W	Wheel Ø 230mm · dead-man switch · No-load 6,600 rpm	See supplied items
CG 15-125 BL	72250660240	1,500 W	Wheel Ø 125mm · lock-on switch · No-load 3,800 - 9,000 rpm	See supplied items
CG 15-125 BL (110 V)	72250660241	110 V · 1,500 W	Wheel Ø 125mm · lock-on switch · No-load 3,800 - 9,000 rpm	See supplied items
CG 15-125 BL Inox	72250760240	1,500 W	Wheel Ø 125mm · lock-on switch · No-load 2,800 - 7,000 rpm	See supplied items
CG 15-125 BL Inox (110 V)	72250760241	110 V · 1,500 W	Wheel Ø 125mm · lock-on switch · No-load 2,800 - 7,000 rpm	See supplied items
CG 15-125 BLP	72250860240	1,500 W	Wheel Ø 125mm · dead-man switch · No-load 3,800 - 9,000 rpm	See supplied items
CG 15-125 BLP (110 V)	72250860241	110 V · 1,500 W	Wheel Ø 125mm · dead-man switch · No-load 3,800 - 9,000 rpm	See supplied items
CG 15-125 BLP Inox	72250960240	1,500 W	Wheel Ø 125mm · dead-man switch · No-load 2,800 - 7,000 rpm	See supplied items

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

GRINDING & FINISHING

Mains Angle Grinders Continued

Compare disc diameter, input and switch type. Use the model page to check guards and supplied fittings.



72250260240

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
CG 15-125 BLP Inox (110 V)	72250960241	110 V · 1,500 W	Wheel Ø 125mm · dead-man switch · No-load 2,800 - 7,000 rpm	See supplied items
CG 15-150 BL	72251060240	1,500 W	Wheel Ø 150mm · lock-on switch · No-load 2,800 - 7,000 rpm	See supplied items
CG 15-150 BL (110 V)	72251060241	110 V · 1,500 W	Wheel Ø 150mm · lock-on switch · No-load 2,800 - 7,000 rpm	See supplied items
CG 15-150 BLP	72251160240	1,500 W	Wheel Ø 150mm · dead-man switch · No-load 2,800 - 7,000 rpm	See supplied items
CG 15-150 BLP (110 V)	72251160241	110 V · 1,500 W	Wheel Ø 150mm · dead-man switch · No-load 2,800 - 7,000 rpm	See supplied items
CG 7-115	72250260240	760 W	Wheel Ø 115mm · No-load 12,500 rpm	See supplied items

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

GRINDING & FINISHING

Die Grinders & Stainless Finishing

Compare collet and speed for internal work, pad diameter for polishing, and belt and pipe dimensions for tube finishing.



71230461000



72231960241



72214924230

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
AGSZ 18-280 BL AS	71230461000	18 V AMPShare	Collet Ø 8mm · No-load 9,000 - 28,000 rpm	Case included
AGSZ 18-280 LBL AS	71230561000	18 V AMPShare	Collet Ø 8mm · No-load 9,000 - 28,000 rpm	Case included
AGSZ 18-90 LBL AS	71230661000	18 V AMPShare	Collet Ø 8mm · Pad Ø 80mm · No-load 2,900 - 9,000 rpm	Case included
GSZ 11-320 PERL (110 V)	72232260241	110 V · 1,010 W	Collet Ø 8mm · No-load 9,500 - 32,500 rpm	See supplied items
GSZ 11-90 PERL (110 V)	72232360241	110 V · 1,010 W	Collet Ø 8mm · Pad Ø 80mm · No-load 2,900 - 9,900 rpm	See supplied items
GSZ 8-280 PEL (110 V)	72231960241	110 V · 750 W	Collet Ø 8mm · No-load 8,500 - 28,000 rpm	See supplied items
GSZ 8-90 PEL (110 V)	72232060241	110 V · 710 W	Collet Ø 8mm · No-load 2,500 - 9,000 rpm	See supplied items
RS 17-70 E	72227560240	1,700 W	Pipe Ø 8 - 80mm · Belt 20/40 x 815mm · No-load 2,700 - 8,500 rpm	—
WPO 14-15 E	72214800230	1,200 W	Pad Ø 230mm · No-load 500 - 1,500 rpm	See supplied items
WPO 14-15 E Set	72214851010	1,200 W	Pad Ø 230mm · No-load 500 - 1,500 rpm	See supplied items
WPO 14-25 E	72214924230	1,200 W	Pad Ø 230mm · No-load 900 - 2,500 rpm	See supplied items

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

GRIT BELT GRINDING

GRIT GKS & GX Systems

Choose GKS for compact belt grinding or GX when you need a modular workshop setup. Check each attachment against the base machine.



79050100403



79012200403



79012400443

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
GRIT GKS 75	79050100403	3 x 400/440V 50/60Hz · 4 kW	Belt 75 x 2,000mm · No-load 3,000 rpm · Weight 50 kg	Compact belt grinder, 75 mm
GRIT GKS 75	79050200232	1 x 230 V · 1.1 kW	Belt 75 x 2,000mm · No-load 3,000 rpm · Weight 45 kg	Compact belt grinder, 75 mm
GRIT GKS 75	79050200403	3 x 400/440V 50/60Hz · 1.5 kW	Belt 75 x 2,000mm · No-load 3,000 rpm · Weight 45 kg	Compact belt grinder, 75 mm
GRIT GKS 75	79050300403	3 x 400/440V 50/60Hz · 3 kW	Belt 75 x 2,000mm · No-load 3,000 rpm · Weight 50 kg	Compact belt grinder, 75 mm
GRIT GKS 75 2H	79050400403	3 x 400/440V 50/60Hz · 1.5 / 2 kW	Belt 75 x 2,000mm · No-load 1,500 / 3,000 rpm · Weight 45 kg	Compact belt grinder, 75 mm
GRIT GX 75	79013100403	3 x 400/440V 50/60Hz · 3 kW	Belt 75 x 2,000mm · No-load 3,000 rpm · Weight 75 kg	Belt grinder (base unit), 75mm
GRIT GX 75 2H	79012200403	3 x 400/440V 50/60Hz · 1.5 / 2 kW	Belt 75 x 2,000mm · No-load 1,730 / 3,450 rpm · Weight 75 kg	Belt grinder (base unit), 75mm, can be switched
GRIT GX 75 2H	79013200403	3 x 400/440V 50/60Hz · 1.5 / 2 kW	Belt 75 x 2,000mm · No-load 1,500 / 3,000 rpm · Weight 75 kg	Belt grinder (base unit), 75mm, can be switched
GRIT GXC	79012300443	3 x 400/440V 50/60Hz · 0.18 kW	Belt 75 x 2,000mm · Pipe Ø 10 - 100mm · Weight 48 kg	Centreless grinding module
GRIT GXE	79010500403	3 x 400/440V 50/60Hz · 2.2 kW	No-load 1,500 rpm · Weight 32 kg	Deburring machine
GRIT GXR	99001001001	—	Belt 75 x 2,250mm · Pipe Ø 16 - 75mm · Stock max. 75 x 75mm · Weight 54 kg	Notch grinding unit
GRIT GXW	79012400443	3 x 400/440V 50/60Hz · 0.12 kW	Weight 8.6 kg	Cooling unit

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

GRIT BELT GRINDING

GRIT GI Machines & Modules

Compare industrial machines and modules for surface, profile and tube work. Match belt dimensions and supply to the exact configuration.



79021700403



79020400403



99001004000

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
GIMS 150 2H	79021700403	3 x 400/440V 50/60Hz · 2.6 / 3.1 kW	Belt 150 x 2,000mm · No-load 1,500 / 3,000 rpm · Weight 114 kg	Mobile carriage
GIMS 150-6	79021900403	3 x 400/440V 50/60Hz · 6 kW	Belt 150 x 2,000mm · No-load 3,000 rpm · Weight 131 kg	Mobile carriage
GIMS 75 2H	79021600403	3 x 400/440V 50/60Hz · 2.6 / 3.1 kW	Belt 75 x 2,000mm · No-load 1,500 / 3,000 rpm · Weight 103 kg	Mobile carriage
GIMS 75-6	79021800403	3 x 400/440V 50/60Hz · 6 kW	Belt 75 x 2,000mm · No-load 3,000 rpm · Weight 121 kg	Mobile carriage
GRIT GI 100	79022300403	3 x 400/440V 50/60Hz · 1.5 kW	Belt 100 x 1,000mm · No-load 3,000 rpm · Weight 28.8 kg	Basic belt grinder, 100 mm
GRIT GI 100 EF	79022300232	1 x 230 V · 1.1 kW	Belt 100 x 1,000mm · No-load 3,000 rpm · Weight 29.8 kg	Basic belt grinder, 100 mm single-phase
GRIT GI 150	79020400403	3 x 400/440V 50/60Hz · 4 kW	Belt 150 x 2,000mm · No-load 3,000 rpm · Weight 82 kg	Belt grinder (base unit), 150mm
GRIT GI 150 2H	79020500403	3 x 400/440V 50/60Hz · 2.6 / 3.1 kW	Belt 150 x 2,000mm · No-load 1,500 / 3,000 rpm · Weight 82 kg	Basic belt grinder, 150 mm switchable
GRIT GI 75	79020100403	3 x 400/440V 50/60Hz · 4 kW	Belt 75 x 2,000mm · No-load 3,000 rpm · Weight 65 kg	Belt grinder (base unit), 75mm
GRIT GI 75 2H	79020200403	3 x 400/440V 50/60Hz · 2.6 / 3.1 kW	Belt 75 x 2,000mm · No-load 1,500 / 3,000 rpm · Weight 65 kg	Belt grinder (base unit), 75mm, can be switched
GRIT GIB	99001003000	—	Weight 17 kg	Stand
GRIT GIBE	99001004000	220/230 & 400/440 V · 0.35 kW	Weight 55 kg	Stand with double dust extraction

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

GRIT BELT GRINDING

GRIT GI Machines & Modules Continued

Check the role of each module, stand and extraction unit before ordering a complete grinding setup.



79021200443



79021300403



99001002000

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
GRIT GIC	79021200443	3 x 400/440V 50/60Hz · 0.18 kW	Belt 75/150 x 2,000mm · Pipe Ø 10 - 130mm · Weight 65 kg	Centreless grinding module
GRIT GIE	79020700403	3 x 400/440V 50/60Hz · 1.5 / 2.0 kW	No-load 1,500 / 3,000 rpm · Weight 34 kg	Deburring machine
GRIT GIL	79024800403	3 x 400/440V 50/60Hz · 0.18 kW	Belt 150 x 2,000mm · Stock max. 100 x 100mm · Weight 64 kg	Linisher modul
GRIT GILS	79025100403	3 x 400/440V 50/60Hz · 2.6 / 3.1 kW	Belt 150 x 2,000mm · Stock max. 100 x 100mm · No-load 1,500 / 3,000 rpm · Weight 206 kg	Longitudinal grinder
GRIT GILSGIB	79023500403	3 x 400/440V 50/60Hz · 2.6 / 3.1 kW	Belt 150 x 2,000mm · Stock max. 100 x 100mm · No-load 1,500 / 3,000 rpm · Weight 189 kg	Longitudinal grinder
GRIT GIMS 150	79021400403	3 x 400/440V 50/60Hz · 4 kW	Belt 150 x 2,000mm · No-load 3,000 rpm · Weight 110 kg	Mobile carriage
GRIT GIMS 75	79021300403	3 x 400/440V 50/60Hz · 4 kW	Belt 75 x 2,000mm · No-load 3,000 rpm · Weight 100 kg	Mobile carriage
GRIT GIR	99001007001	—	Belt 150 x 2,250mm · Pipe Ø 20 - 150mm · Stock max. 120 x 150 mm · Weight 109 kg	Notch grinding unit
GRIT GIS 150	79023050443	3 x 400/440V 50/60Hz · 4 kW	Belt 150 x 2,000mm · No-load 3,000 rpm · Weight 93 kg	Belt grinder, 150mm
GRIT GIS 75	79022950443	3 x 400/440V 50/60Hz · 4 kW	Belt 75 x 2,000mm · No-load 3,000 rpm · Weight 74 kg	Belt grinder
GRIT GIXBE	99001009000	3 x 400/440V 50/60Hz · 0.37 kW	No-load 1,500 / 3,000 rpm · Weight 58 kg	Machine stand with extraction
GRIT GIXS	99001002000	—	Weight 18 kg	Machine stand

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

SAWING & SHEET METAL

Metal Saws

Choose the saw and blade for the stock shape, material and wall thickness. Published cutting capacities use different reference materials.



71350161000



99100001561



75340800000

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
ABAS 18-63 AS cordless band saw	71350161000	18 V AMPShare	Max. depth 63.5mm · Blade 733 x 13 x 0.35mm	Case included
ASAS 18-21 K AS cordless sabre saw	71330161000	18 V AMPShare	Metal profile/pipe 100mm	Case included
Cordless hand-held circular saw F-IRON Cut 57 AS (in box)	99100001560	18 V AMPShare	Steel[1] 24mm · Max. depth 57 mm · Blade Ø 150mm	Boxed tool
Cordless jigsaw F-IRON Jig 26 AS	71360561000	18 V AMPShare	Steel[1] 12mm	Case included
Cordless jigsaw F-IRON Jig 26 AS (in box)	99100001561	18 V AMPShare	Steel[1] 12mm	Boxed tool
F-IRON Cut 57 AS cordless circular saw	71360461000	18 V AMPShare	Steel[1] 24mm · Max. depth 57 mm · Blade Ø 150mm	Case included
PCS 1000 E (110 V)	72342460241	110 V · 700 W	Pipe Ø 440mm	Hacksaws for pipes up to Ø 440mm
STS 325 R	75340800000	1,100 W	Pipe Ø 325 - 440* mm	Hacksaws for pipes up to Ø 440mm

[1] Steel up to 400 N/mm². The general maximum cutting depth and the steel capacity are separate limits.

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

SAWING & SHEET METAL

Nibblers & Shears

Compare capacity at the strength of your sheet. Allow for the cutting path, minimum radius and access for an internal start.



71321061000



71300662000



72324761240

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
ABLK 18 1.3 CSE AS	71321061000	18 V AMPShare	Steel[1] 1.3mm · Steel[2] 0.6mm · Non-ferrous[3] 2mm	Case included
ABLK 18 1.6 E AS	71321161000	18 V AMPShare	Steel[1] 1.6mm · Steel[2] 0.7mm · Non-ferrous[3] 2.5mm	Case included
ABLK 18 1.6 E AS Set	71321162000	18 V AMPShare	Steel[1] 1.6mm · Steel[2] 0.7mm · Non-ferrous[3] 2.5mm	Case included
ABLS 18 1.6 E AS	71300661000	18 V AMPShare	Steel[1] 1.6mm · Steel[2] 1mm · Non-ferrous[3] 2mm	Case included
ABLS 18 1.6 E AS	71300662000	18 V AMPShare	Steel[1] 1.6mm · Steel[2] 1mm · Non-ferrous[3] 2mm	Case included
ABSS 18 1.6 E AS	71300561000	18 V AMPShare	Steel[1] 1.6mm · Steel[2] 0.8mm · Non-ferrous[3] 2mm	Case included
BLK 3.5 E	72324661240	1,700 W	Steel[1] 3.5mm · Steel[2] 1.8mm · Non-ferrous[3] 3.5mm	See supplied items
BLK 5.0 E	72324761240	1,700 W	Steel[1] 5mm · Steel[2] 2.5mm · Non-ferrous[3] 7mm	See supplied items

[1] Steel up to 400 N/mm². [2] Steel up to 800 N/mm². [3] Non-ferrous metals up to 250 N/mm².

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

BEVELLING & PIPE MILLING

Edge Bevelling & Pipe Milling

Match handheld bevellers to the chamfer or radius. For an RSG setup, specify pipe diameter, wall thickness, cutter and site supply.



71380262000



75602400005



73601961000

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
AKFH 18-5 AS	71380262000	18 V AMPShare	Height at 45° 3.5mm · Radius 1.2 / 2,5mm	Case included
AKFH 18-5 AS basic chamfer set	71380561000	18 V AMPShare	Height at 45° 3.5mm · Radius 1.2 / 2,5mm	Case included
RDG 1500 A	75602661000	2,000 W	Feed 40mm/min · Cutter speed 35 rpm	Case included
RDG 1500 B	75602761000	2,000 W	Feed 80mm/min · Cutter speed 70 rpm	Case included
RDG, 18-3a	75602300009	2,000 W	Feed 40mm/min · Cutter speed 35 rpm	Case included
RDG, 18-3b	75602400005	2,000 W	Feed 80mm/min · Cutter speed 70 rpm	Case included
RSG EX 1500 A	73601461000	400 V · 1,500 W	Feed 40mm/min · Cutter speed 35 rpm	Case included
RSG EX 1500 B	73601561000	400 V · 1,500 W	Feed 80mm/min · Cutter speed 70 rpm	Case included
RSG, Ex18a	73601861000	400 V · 1,500 W	Feed 40mm/min · Cutter speed 35 rpm	Case included
RSG, EX18b	73601961000	400 V · 1,500 W	Feed 80mm/min · Cutter speed 70 rpm	Case included

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

OSCILLATING TOOLS

Cordless MULTIMASTER

Use the mount and kit contents to choose between cordless MULTIMASTER variants. Check your existing blades against the tool's Starlock class.



71293862000



71293662000



71293663000

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
Cordless MULTIMASTER AMM 500 Plus AS	71293862000	18 V AMPShare	Mount StarlockPlus · Osc./min 11,000 - 18,500 · Amplitude 2 x 1,7°	Case included
Cordless MultiMaster AMM 500 PLUS AS (in box)	99100001559	18 V AMPShare	Mount StarlockPlus · Osc./min 11,000 - 18,500 · Amplitude 2 x 1,7°	Boxed tool
Cordless MULTIMASTER AMM 500 Plus BLACK EDITION Bare Tool	71294662000	18 V AMPShare	Mount StarlockPlus · Osc./min 11,000 - 18,500 · Amplitude 2 x 1,7°	Case included
Cordless MULTIMASTER AMM 500 Plus Top 4 Ah AS	71293861240	18 V AMPShare	Mount StarlockPlus · Osc./min 11,000 - 18,500 · Amplitude 2 x 1,7°	1 rapid charger GAL 1880 CV AS · 2 battery packs (18 V / 4 Ah)
Cordless MULTIMASTER AMM 500 Plus Top AS	71293863000	18 V AMPShare	Mount StarlockPlus · Osc./min 11,000 - 18,500 · Amplitude 2 x 1,7°	Case included
Cordless MULTIMASTER AMM 700 Max AS	71293662000	18 V AMPShare	Mount StarlockMax · Osc./min 10,000 - 19,500 · Amplitude 2 x 2,0°	Case included
Cordless MultiMaster AMM 700 MAX AS (in box)	99100001558	18 V AMPShare	Mount StarlockMax · Osc./min 10,000 - 19,500 · Amplitude 2 x 2,0°	Boxed tool
Cordless MULTIMASTER AMM 700 MAX BLACK EDITION Bare Tool	71294762000	18 V AMPShare	Mount StarlockMax · Osc./min 10,000 - 19,500 · Amplitude 2 x 2,0°	Case included
Cordless MULTIMASTER AMM 700 Max Top 4 Ah AS	71293661240	18 V AMPShare	Mount StarlockMax · Osc./min 10,000 - 19,500 · Amplitude 2 x 2,0°	1 rapid charger GAL 1880 CV AS · 2 battery packs (18 V / 4 Ah)
Cordless MULTIMASTER AMM 700 Max Top AS	71293663000	18 V AMPShare	Mount StarlockMax · Osc./min 10,000 - 19,500 · Amplitude 2 x 2,0°	Case included

© R H Davey Welding Supplies Ltd · Design and editorial content

OSCILLATING TOOLS

Mains MULTIMASTER

Compare mounting class, mains input and kit configuration for cutting, scraping and sanding.



72296769240

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
MULTIMASTER MM 500 Plus	72296769240	350 W	Mount StarlockPlus · Osc./min 10,000 - 19,500 · Amplitude 2 x 1,7°	Case included
MULTIMASTER MM 500 Plus (110 V)	72296769241	110 V · 350 W	Mount StarlockPlus · Osc./min 10,000 - 19,500 · Amplitude 2 x 1,7°	Case included
MULTIMASTER MM 500 PLUS Selection	72296778240	350 W	Mount StarlockPlus · Osc./min 10,000 - 19,500 · Amplitude 2 x 1,7°	See supplied items
MULTIMASTER MM 500 Plus Top	72296770240	350 W	Mount StarlockPlus · Osc./min 10,000 - 19,500 · Amplitude 2 x 1,7°	Case included
MULTIMASTER MM 500 Plus Top (110 V)	72296770241	110 V · 350 W	Mount StarlockPlus · Osc./min 10,000 - 19,500 · Amplitude 2 x 1,7°	Case included
MULTIMASTER MM 700 Max	72296863240	450 W	Mount StarlockMax · Osc./min 10,000 - 19,500 · Amplitude 2 x 2,0°	Case included
MULTIMASTER MM 700 Max (110 V)	72296863241	110 V · 450 W	Mount StarlockMax · Osc./min 10,000 - 19,500 · Amplitude 2 x 2,0°	Case included
MULTIMASTER MM 700 Max Top	72296864240	450 W	Mount StarlockMax · Osc./min 10,000 - 19,500 · Amplitude 2 x 2,0°	Case included
MULTIMASTER MM 700 Max Top (110 V)	72296864241	110 V · 450 W	Mount StarlockMax · Osc./min 10,000 - 19,500 · Amplitude 2 x 2,0°	Case included
MULTIMASTER MM 700 PLUS Selection	72296865240	450 W	Mount StarlockMax · Osc./min 10,000 - 19,500 · Amplitude 2 x 2,0°	Case included

Use the order-code link for the supplied blades. StarlockMax and the automotive 12-sided mount use different tooling.

© R H Davey Welding Supplies Ltd · Design and editorial content

OSCILLATING TOOLS

Automotive MULTIMASTER

The automotive tools use a 12-sided holder for vehicle glazing and related specialist work. Match the blade profile to the seal and access.



72297064240

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
Cordless MULTIMASTER AMM 700 1.7 Q AS	71293761000	18 V AMPShare	Mount 12-sided · Osc./min 10,000 - 19,500 · Amplitude 2 x 1,7°	Case included
Cordless MULTIMASTER AMM 700 1.7 Q Autoglas AS	71293762240	18 V AMPShare	Mount 12-sided · Osc./min 10,000 - 19,500 · Amplitude 2 x 1,7°	1 rapid charger GAL 1880 CV AS · 2 battery packs (18 V / 5 Ah)
MULTIMASTER MM 700 1.7 Q Autoglas	72297062240	450 W	Mount Hexagon · Osc./min - · Amplitude 2 x 1,7°	Case included
MULTIMASTER MM 700 1.7 Q Basic	72296963240	450 W	Mount 12-sided · Osc./min 10,000 - 19,500 · Amplitude 2 x 1,7°	Case included
MULTIMASTER MM 700 1.7 Q Basic (110 V)	72296963241	110 V · 450 W	Mount 12-sided · Osc./min 10,000 - 19,500 · Amplitude 2 x 1,7°	Case included
MULTIMASTER MM 700 1.7 Q Bus & Truck	72297064240	450 W	Mount 12-sided · Osc./min 10,000 - 19,500 · Amplitude 2 x 1,7°	Case included

Use the order-code link for the supplied blades. StarlockMax and the automotive 12-sided mount use different tooling.

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

EXTRACTION & WORKHOLDING

Wet and Dry Extractors

Choose the dust class required by the application before comparing tank capacity, airflow and the supplied hose or filter.



92604203010



92036211240



92032060241

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
ASBS 18-10 AS	92604203010	18 V AMPShare	Tank 10 l	1 hose
FEIN Dustex 25 L	92035223240	1,380 W	Tank 22 l · Airflow 4,320 l/min · Vacuum 253 hPa	1x 4 m suction hose, diameter 35mm
FEIN Dustex 25 L (110 V)	92035211240	110 V · 1,380 W	Tank 22 l · Airflow 4,320 l/min · Vacuum 253 hPa	1x 4 m suction hose, diameter 35mm
FEIN Dustex 35 L	92036223240	1,380 W	Tank 32 l · Airflow 4,320 l/min · Vacuum 253 hPa	1x 4 m suction hose, diameter 35mm
FEIN Dustex 35 L (110 V)	92036211240	110 V · 1,380 W	Tank 32 l · Airflow 4,320 l/min · Vacuum 253 hPa	1x 4 m suction hose, diameter 35mm
FEIN Dustex 35 LX AC	92030060240	1,380 W	Tank 35 l · Airflow 4,320 l/min · Vacuum 254 hPa	1x 4 m suction hose, diameter 35mm
FEIN Dustex 35 LX AC (110 V)	92030060241	110 V · 1,380 W	Tank 35 l · Airflow 4,320 l/min · Vacuum 254 hPa	1x 4 m suction hose, diameter 35mm
FEIN Dustex 35 MX AC	92032060240	1,380 W	Tank 35 l · Airflow 4,320 l/min · Vacuum 254 hPa	1x 4 m ES suction hose, diameter 35mm
FEIN Dustex 35 MX AC (110 V)	92032060241	110 V · 1,380 W	Tank 35 l · Airflow 4,320 l/min · Vacuum 254 hPa	1x 4 m ES suction hose, diameter 35mm

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

EXTRACTION & WORKHOLDING

VersaMAG & Sealant Application

Choose the VersaMAG base and clamping attachment by the workpiece. Match the sealant gun to the cartridge or foil pouch capacity.



90701007000



90701003020



71460161000

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
FEIN VersaMAG core drilling Set MK3	90701007000	—	Clamp 108mm · Holding force 7,800 N · Jaw 100mm	Case included
FEIN VersaMAG VISE 160 L SET magnetic vice	99100001357	—	Clamp 160mm · Holding force 12,500 N · Jaw 150mm	Magnetic vise with a clamping width of 160 mm and jaw width of 150mm
FEIN VersaMAG vise set	90701003020	—	Clamp 108mm · Holding force 7,800 N · Jaw 100mm	Magnetic vice with a jaw width of 100mm.
FEIN VersaMAG Vise Set including aluminum jaw protectors	90701009000	—	Clamp 108mm · Holding force 7,800 N · Jaw 100mm	Case included
AKP 18-600 AS	71460161000	18 V AMPShare	Cartridge 310, 400 ml · Pouch 300, 400, 600 ml · Force 3 500 N	Cordless sealant gun

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

EXTRACTION & WORKHOLDING

Tool Balancers

Match the rated load range to the weight of the suspended tool and fittings. Compare cable travel and mounting requirements.



90801012008



90801055000

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
Balancer up to 1.5 kg	90801012008	—	Variable load 0.5 -1.5 kg · Weight 0.35 kg	—
Balancer up to 1.5 kg	90801052004	—	Variable load 0.5 -1.5 kg · Weight 0.35 kg	—
Balancer up to 11 kg	90801028008	—	Variable load 7.5 -11 kg · Weight 3.2 kg	—
Balancer up to 14 kg	90801029002	—	Variable load 10 -14 kg · Weight 3.2 kg	—
Balancer up to 17 kg	90801030004	—	Variable load 13.5 -17 kg · Weight 3.2 kg	—
Balancer up to 2,5 kg	90801023001	—	Variable load 1.5 -2.5 kg · Weight 0.35 kg	—
Balancer up to 2,5 kg	90801037009	—	Variable load 1.5 -2.5 kg · Weight 0.35 kg	—
Balancer up to 25 kg	90801055000	—	Variable load 13 -25 kg · Weight 11.2 kg	—

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

EXTRACTION & WORKHOLDING

Tool Balancers Continued

Check the load range, cable travel and mounting requirements for the exact model.



90801027000

MODEL / KIT	FEIN ORDER CODE	SUPPLY / INPUT	CAPACITY / SETUP	SUPPLIED / TYPE
Balancer up to 3 kg	90801024009	—	Variable load 1 -3 kg · Weight 3.2 kg	—
Balancer up to 32 kg	90801056000	—	Variable load 22 -32 kg · Weight 11.5 kg	—
Balancer up to 45 kg	90801057000	—	Variable load 30 -45 kg · Weight 12 kg	—
Balancer up to 5 kg	90801025003	—	Variable load 2.5 -5 kg · Weight 3.2 kg	—
Balancer up to 6,5 kg	90801026006	—	Variable load 3.5 -6.5 kg · Weight 3.2 kg	—
Balancer up to 60 kg	90801058000	—	Variable load 45 -60 kg · Weight 12.4 kg	—
Balancer up to 9 kg	90801027000	—	Variable load 4.5 -9 kg · Weight 3.2 kg	—

FEIN UK accessories

© R H Davey Welding Supplies Ltd · Design and editorial content

CORDLESS POWER

Batteries and Chargers

Match the battery interface on the machine. AMPShare 18 V and the FEIN MultiVolt system have separate product listings.

Check the kit before buying a charger

Read the supplied-items list on the exact tool page. For demanding cordless work, check FEIN's battery recommendation for the model before choosing capacity.

AMPSHARE 18 V	FEIN ORDER CODE	CAPACITY / FORMAT
ProCORE18V battery	92604341020	4 Ah
ProCORE18V battery	92604342020	8 Ah
ProCORE18V battery	92604343020	12 Ah
GBA 18V battery	92604345020	4 Ah
GBA 18V battery	92604346020	5 Ah
GAL 1880 CV charger	92604333010	Charger
GAL 18V-160 charger	92604337010	Charger
ProCORE18V starter set	92604228240	4 Ah
ProCORE18V starter set	92604229240	8 Ah
ProCORE18V starter set	92604241240	12 Ah
GBA 18V starter set	92604246240	5 Ah

FEIN BATTERY PACKS	FEIN ORDER CODE	CAPACITY / FORMAT
FEIN battery pack	92604182020	18 V · 3 Ah
FEIN battery pack	92604175020	18 V · 6 Ah
FEIN HighPower battery pack	92604179020	18 V · 5.2 Ah
FEIN battery pack	92604183020	12 V · 3 Ah

FEIN battery and charger catalogue

FEIN AMPShare system

© R H Davey Welding Supplies Ltd · Design and editorial content

ORDERING & COMPATIBILITY

Tooling and Accessories

Use the machine order code when choosing tooling, spares or a second setup. The manufacturer accessory finder links the machine to compatible options.

TOOL FAMILY	WHAT TO MATCH
Magnetic core drills	Cutter diameter and depth, holder or adapter, pilot pin and coolant delivery.
Drill/drivers and fastening	QuickIN or fixed chuck interface, bit or socket drive and the required torque range.
Angle and die grinders	Disc diameter, bore or thread, maximum permissible speed, guard and collet size.
GRIT belt grinding	Base family, belt width and length, module, stand and extraction setup.
Saws, shears and nibblers	Blade or punch and die set, stock strength, thickness and cutting path.
Bevelling and pipe milling	Cutter profile, insert, pipe size, guide system and machine variant.
MULTIMASTER	Starlock, StarlockPlus, StarlockMax or the automotive 12-sided holder.
Extraction	Dust class, filter and bag compatibility, hose and tool adapter.
VersaMAG	Base, jaw type, jaw opening and compatible clamping attachment.

FEIN accessory finder

FEIN Starlock compatibility

Specify your setup

Send the order code, material and dimensions, the operation you need to carry out, and your available supply or existing battery system. Include any accessories or consumables you want with the machine.

© R H Davey Welding Supplies Ltd · Design and editorial content