JASIC / MIG / EVO

EVO MIG 350 S

MIG/MAG / MMA / DC LIFT TIG

Separate feeder / Water-cooled

EM-350S-WC



Where it fits

350 A for three-phase fabrication with a separate feeder. The LC-60 cooler supports a water-cooled torch for longer runs.

- Separate four-roll feeder for work away from the power source.
- Manual and synergic MIG/MAG with MMA and DC Lift TIG.
- Optional spool gun or push-pull torch for compatible wire setups.

Package and options

ITEM	DETAIL
Included	Mig Torch (HC550-4E), 5m Interconnection Cable, 3m Earth Clamp, Separate WFU, Argon Regulator, Gas Hose, Trolley, Water Cooler (LC-60)
Options	Wireless Remote Control (HRC-02), Wired Remote Control (HRC-01), Mobile Bluetooth App Module (51009435), Spool On Gun, Push Pull Torch, 10m, 15m, 20m Interconnection Cable
For large assemblies	Choose the interconnection length to put the feeder close to the joint. Match cooling type to the torch package.

Output and setup data

RATING	VALUE
Input supply	400 V AC, three-phase
MIG output	30–350 A
MIG duty at 40°C	350 A at 50%
Wire setup	D300 spool / 4-roll feeder
MIG input	14 A effective (Ieff) · 14.6 kVA rated power
MMA input	15 A effective (Ieff) · 15.2 kVA rated power
Lift TIG input	10.8 A effective (Ieff) · 11.1 kVA rated power
AVR generator	22.5 kVA
Wire feed speed	2-24 m/min
Protection	IP23S
L × W × H	1060 × 550 × 1290mm
Weight	95 kg

Duty cycle is the share of a 10-minute period at the stated current and test temperature.

Jasic technical reference

Jasic product information

© R H Davey Welding Supplies Ltd · Design and editorial content