JASIC / EVO

EVO TIG 200P AC/DC PFC

AC/DC pulse TIG / MMA

Air-cooled torch

ET-200PACDC



Where it fits

For a workshop switching between aluminium, stainless and mild steel without changing power source.

- AC waveforms and adjustable balance for aluminium
- Pulse TIG with HF and Smart Lift starting
- Wide-voltage PFC and optional TFT display

Technical data

Supply	95–265 V AC, single-phase
TIG current	DC 5–160 / 5–200 A · AC 20–160 / 20–200 A*
TIG duty at 40°C	160 A at 25% (115 V) / 200 A at 25% (230 V)
MMA range	10–120 A (115 V) / 10–160 A (230 V)
Protection	IP23S
L × W × H	490 × 165 × 341 mm
Weight	11.9 kg power source

* TIG ranges are given at 115 V and 230 V, in that order.

Package includes

4 m TIG torch, lead set, gas hose and argon regulator.

Options and setup

Compatible foot pedal or hand remote, plus the optional TFT screen. LC-30 cooler available.

Technical leaflet **Operator manual** **View product online**

5-year warranty subject to Jasic UK registration and terms.

R H DAVEY WELDING SUPPLIES LTD
67-69 Quayside Road, Southampton SO18 1AE

02380 339443 · sales@rhdaveywelding.co.uk
rhdaveywelding.co.uk