JASIC / MIG / PRO

PRO MIG 250 PULSE

PULSE MIG/MAG / MMA / DC LIFT TIG

Compact / Single pulse

JM-250P



Where it fits

For a single-phase fabrication bay that needs single-pulse MIG for aluminium or jobs that benefit from controlled heat input.

- Single-pulse and synergic MIG settings.
- Four-roll drive and spool gun option.
- MMA and DC Lift TIG modes for secondary work.

Package and options

ITEM	DETAIL
Included	MIG Welding Torch (HC300-4E), Work Return Lead and Clamp, Gas Hose and Regulator (SSARG2G), Trolley
Options	MMA Leads (WCS25-3WEL), Spool Gun (TSP-250-P)

Output and setup data

RATING	VALUE
Input supply	230 V AC, single-phase
MIG output	40–250 A
MIG duty at 40°C	250 A at 40%
Wire setup	4-roll drive / 1.5–16 m/min
MIG input	29.2 A effective (Ieff) · 9.13 kVA rated power
Protection	IP21S
L × W × H	895 × 455 × 760mm
Weight	49.7 kg

Duty cycle is the share of a 10-minute period at the stated current and test temperature.

Jasic technical reference

Jasic product information

© R H Davey Welding Supplies Ltd · Design and editorial content