JASIC / MIG / PRO

PRO MIG 270 SEPARATE

MIG/MAG / MMA

Separate feeder / Water-cooled

JM-272S-WC



Where it fits

A single-phase 270 A package with a separate feeder and water cooling for longer torch-on work.

- Four-roll separate feeder with 5 m interconnection.
- Burnback and inductance settings for MIG setup.
- Wire inching, gas check and 2T/4T trigger selection.

Package and options

ITEM	DETAIL
Included	4 Roll Wire Feed Unit, MIG Welding Torch (T501-4), 5m Interconnecting Cable, Work Return Lead and Clamp, Gas Hose and Regulator, Trolley, Water Cooler, Cooling Fluid
Options	MMA Leads (WCS25-3WEL)

Output and setup data

RATING	VALUE
Input supply	230 V AC, single-phase
MIG output	30–270 A
MIG duty at 40°C	270 A at 30%
Wire setup	4-roll feeder / 0.6–1.2mm wire
MIG input	28.9 A effective (Ieff) · 12.1 kVA rated power
Protection	IP21S
L × W × H	1020 × 505 × 1460mm
Weight	122 kg

Duty cycle is the share of a 10-minute period at the stated current and test temperature.

Jasic technical reference

Jasic product information

© R H Davey Welding Supplies Ltd · Design and editorial content