JASIC / MIG / PRO

PRO MIG 500 PULSE

PULSE MIG/MAG / MMA

Separate feeder / Water-cooled

JM-500P



Where it fits

For heavy three-phase fabrication that calls for 500 A pulse MIG output, a separate feeder and water cooling.

- Pulse and synergic MIG/MAG.
- Separate four-roll drive with 5 m interconnection.
- Water-cooled torch package for high-current work.

Package and options

ITEM	DETAIL
Included	4 Roll Wire Feed Unit (JM-WF500P-5), MIG Welding Torch (HC550-4E), 5m Interconnecting Cable, Work Return Lead and Clamp, Gas Hose and Regulator (SSARG2G), Trolley, Water Cooler, Cooling Fluid
Options	MMA Leads (WCS25-3WEL), 10m, 15m, 20m Interconnection Cable
For large assemblies	Choose the interconnection length to put the feeder close to the joint. Match cooling type to the torch package.

Output and setup data

RATING	VALUE
Input supply	400 V AC, three-phase
MIG output	30–500 A
MIG duty at 40°C	500 A at 50%
Wire setup	Separate 4-roll feeder
MIG input	28.6 A effective (Ieff) · 26.7 kVA rated power
Protection	IP23S
L × W × H	1080 × 510 × 1180mm
Weight	129 kg

Duty cycle is the share of a 10-minute period at the stated current and test temperature.

Jasic technical reference

Jasic product information

© R H Davey Welding Supplies Ltd · Design and editorial content